



SIC279

134.2 kHz, Multi-Purpose R/W HDX RFID IC with 192 bits of User Memory
REV 1.1

Features Summary

Highlight Features

- New improvement from its predecessor to fully support
- Industrial application (BDE format)
- Customizable, long read range R/W RFID transponder
- Half duplex FM telegram 124/134 kHz contactless read/write data

Interface and Peripheral

- Compliant with BDE format (for waste management application)
- Fully compliant with ISO 11784/11785 HDX R/O Animal tag
- ID data protocol/structure
- Fully compliant with mainstream HDX R/W ID format

Memory

- R/W user memory of 6X32 (192 bits)
- Supporting user access to factory unique ROM ID (UID), preventing chips from cloning
- Direct Access/Write Mode
- Protected Direct Access/Write Mode
- One-time programming (OTP) configuration
- Write endurance > 100,000 R/W cycles
- Memory retention > 20 years

Commands

- Proprietary command protocol
- Comprehensive error logging reports
- Support cascade commands

Operating Conditions

- Carrier frequency f_c is 134.2 kHz
- Operating temperature: -25°C to 85°C

Package

- Glass Transponder 32 mm

Applications

- HDX industrial application
- Waste bin tag (BDE)
- HDX ISO 11784/85 Animal Tag, ICAR compliant RFID tags
- Long Read-Range EAS Transponders



Revision History

Revision	Date	Change/Update Comment
1.0	10 Oct 2024	Official Release
1.1	5 Jun 2025	<ul style="list-style-type: none">• Update document template• Update ordering information

Ordering information

Part No.	Description	Configuration	Package	Standard Packing
P29AGU54G20SU2920C1	SIC279-20, LF HDX IC with RW memory 512 bits and Industrial ID Glass tag 134.2kHz, Canister, RFID TAG	Standard	Glass tube 32mm (Transparent epoxy)	100 pcs/Canister
P29AGU54G10SU2920C2	SIC279-20, LF HDX IC with RW memory 512 bits and Industrial ID Glass tag 134.2kHz, Canister, RFID TAG	Standard	Glass tube 32mm (Black epoxy)	1,000 pcs/Canister
P29AGU54G10SU2922C2	SIC279-22, LF HDX IC with RW memory 512 bits and Industrial ID Glass tag 134.2kHz, Canister, RFID TAG	Custom #22	Glass tube 32mm (Black epoxy)	1,000 pcs/Canister
P29AGU54G10SU2926C2	SIC279-26, LF HDX IC with RW memory 512 bits and Industrial ID Glass tag 134.2kHz, Canister, RFID TAG	Custom #26	Glass tube 32mm (Black epoxy)	1,000 pcs/Canister
P29AGU54G10SU2927C2	SIC279-27, LF HDX IC with Industrial ID - Read only Glass tag 134.2kHz, Canister, RFID TAG	Custom #27	Glass tube 32mm (Black epoxy)	1,000 pcs/Canister
P29AGU54G20SU2913C1	SIC279-13, LF HDX IC with Animal ID - Read only Glass tag 134.2kHz, Canister, RFID TAG	Custom #13	Glass tube 32mm (Transparent epoxy)	100 pcs/Canister
P29AGU54G10SU2914C1	SIC279-14, LF HDX IC with Animal ID - Read only Glass tag 134.2kHz, Canister, RFID TAG	Custom #14	Glass tube 32mm (Black epoxy)	100 pcs/Canister
P29AGU54G10SU2915C2	SIC279-15, LF HDX IC with Animal ID - Read only Glass tag 134.2kHz, Canister, RFID TAG	Custom #15	Glass tube 32mm (Black epoxy)	1,000 pcs/Canister
P29AGU54G20SU2916C2	SIC279-16, LF HDX IC with Animal ID - Read only Glass tag 134.2kHz, Canister, RFID TAG	Custom #16	Glass tube 32mm (Transparent epoxy)	1,000 pcs/Canister
P29AGU54G20SU2917C2	SIC279-17, LF HDX IC with RW memory 512 bits and Animal ID Glass tag 134.2kHz, Canister, RFID TAG	Custom #17	Glass tube 32mm (Transparent epoxy)	1,000 pcs/Canister

The information herein is for product information purpose. While the contents in this publication have been carefully checked; no responsibility, however, is assumed for inaccuracies. Silicon Craft Technology PLC. reserves the right to make changes to the products contained in this publication in order to improve design, performance or reliability.

Package information




Figure 1: Drawing and dimension

Table 1: Package specifications

Item	Parameter	Value	Tolerance	Unit
Glass Transponder	Length	31.50	± 0.50	mm
	Width	3.85	± 0.20	mm

Disclaimer

- The information described herein is subject to change without notice.
- Although the IC contains a static electricity protection circuit, static electricity or voltage that exceeds the limit of the protection circuit should not be applied.
- Silicon Craft Technology assumes no responsibility for the way in which this IC is used in products created using this IC or for the specifications of that product, nor does Silicon Craft Tech. Assume any responsibility for any infringement of patents or copyrights by products that include this IC either in Thailand or in other countries.
- Silicon Craft Technology is not responsible for any problems caused by circuits or diagrams described herein whose related industrial properties, patents, or other rights belong to third parties. The application circuit examples explain typical applications of the products, and do not guarantee the success of any specific mass-production design.
- Use of the information described herein for other purposes and/or reproduction or copying without the express permission of Silicon Craft Technology is strictly prohibited.
- The products described herein cannot be used as part of any device or equipment affecting the human body, such as exercise equipment, medical equipment, security systems, gas equipment, or any apparatus installed in airplanes and other vehicles, without prior written permission of Silicon Craft Technology.
- Although Silicon Craft Technology exerts the greatest possible effort to ensure high quality and reliability, the failure or malfunction of semiconductor products may occur. The user of these products should therefore give thorough consideration to safety design, including redundancy, fire-prevention measures, and malfunction prevention, to prevent any accidents, fires, or community damage that may ensue.